

Belarus Cardigan

pattern correction

Cabled Eyelet Stitch pattern

Row 2: K2, *p1, yo, p1, k1, p3, k1 * to last 6 sts, p1, yo, p1, k1, p3.

YOKE

Next Row (WS): Work 3 sts in Incorporated I-cord, p20 (22, 23, 24, 25) for right front, pm, p16 (18, 18, 18, 18) for right sleeve, pm p36 (40, 42, 44, 46) for back, pm, p16 (18, 18, 18, 18) for left sleeve, pm, p20 (22, 23, 24, 25) for left front, work 2 sts in Incorporated I-cord.

RAGLAN SHAPING

Sizes S (M, -, -, -) only:

Next Row (RS, inc): *Work to 2 sts before m, kfb, k1, sl m, kfb; rep from * 3 more times, work to end. [8 sts inc'd]

Work 3 rows even, ending with a WS row.

Rep the last 4 rows 4 (0, -, -, -) more times. [154 (134, -, -, -) sts]

All Sizes:

Next Row (WS, inc): *Work to 2 sts before m, pfb, p1, sl m, pfb; rep from * 3 more times, work to end. [8 sts inc'd]

Work 2 rows even, ending with a WS row.

Rep the last 6 rows 2 (5, 4, 3, 2) more times [202 (230, 210, 198, 186) sts]

Sizes - (-, L, XL, 2XL) only: Next Row (RS, inc): *Work to 2 sts before m, kfb, k1, sl m, kfb; rep from * 3 more times, work to end. [8 sts in'd] Work 1 row even.

Rep the last 2 rows - (-, 5, 10, 15) more times. [- (-, 258, 286, 314) sts]

All Sizes:

202 (230, 258, 286, 314 sts; 34 (38, 42, 46, 50) sts each front; 38 (44, 50, 56, 62) sts each sleeve and 58 (66, 74, 82, 90) sts for back.

Divide Body and Sleeves (RS): Work to m, remove m, place next 38 (44, 50, 56, 62) sleeve sts onto waste yarn, provisionally CO 6 (7, 8, 9, 10) sts for underarm placing marker for side after first 3 (4, 4, 5, 5) CO sts, remove next m, work to m, remove m, place next 38 (44, 50, 56, 62) sleeve sts onto waste yarn, provisionally CO 6 (7, 8, 9, 10) sts for underarm placing marker for side after first 3 (3, 3, 4, 4, 5) CO sts, remove next m and work to end. [138 (156, 174, 192, 210) sts; 37 (42, 46, 51, 55) sts each front; 64 (72, 82, 90, 100) sts for back]

BODY

Side Shaping

Work 19 (21, 21, 23, 23) rows even, ending with a WS row.

Next Row (RS, inc): *Work to 2 sts before m, kfb, k1, sl m, kfb; rep from * once more, work to end. [4 sts inc'd]

Pocket (make 2)

CO 3 sts onto dpn. With working yarn, work I-cord for 24 rows. Rotate I-cord sideways, skip first 2 rows, then pick up 22 sts into each row alongside one st-column of the I-cord. [25 sts]

Set-up Row (WS): K2, *p3, k1; rep from * to last 3 sts, p3. Work Rows 1-4 of Cable Eyelet Patt 8 tiems, then work rows 1-2 once again.

Slip first 3 sts onto an empty dpn, work Regular I-cord on those 3 sts for 2 rows. With RS facing, work Applied I-cord Bind off.

FRONT LINING (OPTIONAL)

Using grosgrain ribbon stabilize both fronts by sewing it on the inside fronts along Incorporated I-cords. Sew them on, starting below the collar, using whip stitch and sewing needle with matching thread.